

UNITED STATES PATENT AND TRADEMARK OFFICE  
DOCUMENT CLASSIFICATION BARCODE SHEET

---



000

CATEGORY:

CLEARED

---

ADDRESS  
CONTACT IF FOUND:

FORM PTO-1390 (Modified) (REV 11-98)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER NAK1-BN65	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR <b>09/744227</b>	
INTERNATIONAL APPLICATION NO. <b>PCT/JP00/03154</b>		INTERNATIONAL FILING DATE <b>May 17, 2000</b>		PRIORITY DATE CLAIMED <b>May 20, 1999</b>	
TITLE OF INVENTION <b>METHOD OF PRODUCING GAS DISCHARGE PANEL</b>					
APPLICANT(S) FOR DO/EO/US <b>Hidetaka Hiroshino et al.</b>					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
<ol style="list-style-type: none"> <li>1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371.</li> <li>3. <input type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).</li> <li>4. <input type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.</li> <li>5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371 (c) (2)) <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau).</li> <li>b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau.</li> <li>c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US).</li> </ol> </li> <li>6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)).</li> <li>7. <input checked="" type="checkbox"/> A copy of the International Search Report (PCT/ISA/210).</li> <li>8. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 (c)(3)) <ol style="list-style-type: none"> <li>a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau).</li> <li>b. <input type="checkbox"/> have been transmitted by the International Bureau.</li> <li>c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired.</li> <li>d. <input checked="" type="checkbox"/> have not been made and will not be made.</li> </ol> </li> <li>9. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).</li> <li>10. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).</li> <li>11. <input type="checkbox"/> A copy of the International Preliminary Examination Report (PCT/IPEA/409).</li> <li>12. <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).</li> </ol>					
Items 13 to 20 below concern document(s) or information included:					
<ol style="list-style-type: none"> <li>13. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98.</li> <li>14. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.</li> <li>15. <input checked="" type="checkbox"/> A <b>FIRST</b> preliminary amendment.</li> <li>16. <input type="checkbox"/> A <b>SECOND</b> or <b>SUBSEQUENT</b> preliminary amendment.</li> <li>17. <input type="checkbox"/> A substitute specification.</li> <li>18. <input type="checkbox"/> A change of power of attorney and/or address letter.</li> <li>19. <input checked="" type="checkbox"/> Certificate of Mailing by Express Mail</li> <li>20. <input checked="" type="checkbox"/> Other items or information:</li> </ol>					
<div style="border: 1px solid black; padding: 5px;"> Copy of PCT Request  Copy of International Publication </div>					

09/744227

PCT/JP00/03154

NAK1-BN65

1002 Rec'd PCT/PTO 22 JAN 2001

21. The following fees are submitted:

**BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :**

- ☐ Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO ..... \$1,000.00
- ☒ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... \$860.00
- ☐ International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... \$710.00
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... \$690.00
- ☐ International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) ..... \$100.00

**ENTER APPROPRIATE BASIC FEE AMOUNT =**

\$860.00

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (e)).

\$0.00

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	49 - 20 =	29	x \$18.00
Independent claims	3 - 3 =	0	x \$80.00

\$522.00

\$0.00

Multiple Dependent Claims (check if applicable). ☐

\$0.00

**TOTAL OF ABOVE CALCULATIONS =**

\$1,382.00

Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28) (check if applicable). ☐

\$0.00

**SUBTOTAL =**

\$1,382.00

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492 (f)).

\$0.00

**TOTAL NATIONAL FEE =**

\$1,382.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31) (check if applicable). ☒

\$40.00

**TOTAL FEES ENCLOSED =**

\$1,422.00

Amount to be:  
refunded \$  
charged \$

☒ A check in the amount of \$1,422.00 to cover the above fees is enclosed.

☐ Please charge my Deposit Account No. \_\_\_\_\_ in the amount of \_\_\_\_\_ to cover the above fees.  
A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. **16-2462** A duplicate copy of this sheet is enclosed.

**NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:

Joseph W. Price, Reg. No. 25,124  
PRICE AND GESS  
2100 S.E. Main St., Ste. 250  
Irvine, CA 92614  
Tel: 949/261-8433  
Fax: 949/261-9071

SIGNATURE

Joseph W. Price

NAME

25,124

REGISTRATION NUMBER

January 22, 2001

DATE

09/744227

NAK1-BN65

301 PCT/PTO 22 JAN 2001

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Application of:

Hidetaka Higashino et al.

Serial No.:

Filed:

For: METHOD OF PRODUCING GAS  
DISCHARGE PANEL

Examiner:

Group Art Unit:

Irvine, CA 92614

January 19, 2001

**PRELIMINARY AMENDMENT**

Assistant Commissioner for Patents  
Washington, D.C. 20231

Dear Sir:

Prior to an examination on the merits of the above-identified application, please enter the following amendments:

**IN THE CLAIMS:**

Please amend the claims as follows:

Claim 41, line 2, delete "one of Claims 1 to 40" and insert --Claim 1--;

Claim 44, line 2, delete "one of Claims 1 to 40" and insert --Claim 1--.

Please add the following newly-drafted Claims 48 and 49.



## REMARKS


The amendments to the claims are to remove multiple dependency and to correct minor grammatical errors.

Newly drafted Claims 48 and 49 are within the scope of the original invention and do not add any new subject matter.

If the Examiner believes that a telephone interview will help further the prosecution of this case, he is respectfully requested to contact the undersigned attorney at the listed telephone number.

Very truly yours,

PRICE AND GESS



\_\_\_\_\_  
Joseph W. Price, Reg. 251,24  
2100 S.E. Main St., Ste. 250  
Irvine, CA 92614  
949/261-8433

8/PRJ

09/744227

J602 Rec'd PCT/PTO 22 JAN 2001

DESCRIPTION

Method of Producing Gas Discharge Panel

5 FIELD OF THE INVENTION

The present invention relates to the method of producing the gas discharge panel such as the plasma display panel used for displaying images on computer and TV monitors.

10

BACKGROUND OF THE INVENTION

An explanation of the conventional plasma display panel will be given with reference to figures. Fig. 8 is a simplified sectional view of the AC plasma display panel (hereinafter, referred to "PDP").

15

In Fig. 8, a reference number 110 indicates a front glass plate. On the front glass plate 110, display electrodes 111 are formed. The display electrodes 111 are covered by a dielectric glass layer 112 and a dielectric protection layer 113 made of magnesium oxide (MgO) (refer to Japanese Patent Laid-Open Publication No. 5-342991).

20

Meanwhile, a reference number 120 indicates a back glass plate. On the back glass plate 120, address electrodes 121, a visible light reflective layer 122 for covering the address electrodes 121, partition walls 123,

25

and phosphor layers 124 are disposed. A reference number 130 indicates a discharge space filled with a discharge gas. For color display, each of the phosphor layers 124 is red, green or blue and the phosphor layers 124 are disposed in this order. Each of the phosphor layers 124 is excited by short ultraviolet light of a short wavelength (for instance, 147nm) that has been generated by discharge and emits light.

Generally, the phosphors described below are used for the phosphor layers 124.

"Blue phosphor":  $\text{BaMgAl}_{10}\text{O}_{17}:\text{Eu}$

"Green phosphor":  $\text{Zn}_2\text{SiO}_4:\text{Mn}$  or  $\text{BaAl}_{12}\text{O}_{19}:\text{Mn}$

"Red phosphor":  $\text{Y}_2\text{O}_3:\text{Eu}$  or  $(\text{Y}_x\text{Gd}_{1-x})\text{BO}_3:\text{Eu}$

Now, the method of producing each of the phosphors will be described.

The blue phosphor ( $\text{BaMgAl}_{10}\text{O}_{17}:\text{Eu}$ ) is manufactured as follows. First, barium carbonate ( $\text{BaCO}_3$ ), magnesium carbonate ( $\text{MgCO}_3$ ), and aluminium oxide ( $\alpha\text{-Al}_2\text{O}_3$ ) are blended so that the atomic ratio of barium (Ba), magnesium (Mg), and aluminium (Al) is 1:1:10.

Next, a predetermined amount of europium oxide ( $\text{Eu}_2\text{O}_3$ ) is added to the mixture. Then, the mixture is blended with an appropriate amount of flux ( $\text{AlF}_3$ ,  $\text{BaCl}_2$ ) in a ball mill. The mixture that has been blended with the flux is calcinated at 1400 to 1650°C for a predetermined amount of time (for instance, 0.5 hours) in



a reducing atmosphere (in  $H_2$  or  $N_2$ ) to obtain the blue phosphor.

The red phosphor ( $Y_2O_3:Eu$ ) is manufactured as follows. The raw materials for the red phosphor, yttrium hydroxide ( $Y_2(OH)_3$ ) and boric acid ( $H_3BO_3$ ) are blended so that the atomic ratio between yttrium and boric is 1:1. Then, a predetermined amount of europium oxide ( $Eu_2O_3$ ) is added to the mixture. The mixture is blended with an appropriate amount of flux in a ball mill and is calcinated at 1200 to 1450°C for a predetermined amount of time (for instance, 1.0 hour) in the air to obtain the red phosphor.

The green phosphor ( $Zn_2SiO_4:Mn$ ) is manufactured as follows. The raw materials for the green phosphor, zinc oxide ( $ZnO$ ) and silicon oxide ( $SiO_2$ ) are blended so that the atomic ratio between zinc and silicon is 2:1. Then, a predetermined amount of manganese oxide ( $Mn_2O_3$ ) is added to the mixture and blended in a ball mill. The mixture is calcinated at 1200 to 1350°C for a predetermined amount of time (for instance, 0.5 hours) in the air to obtain the red phosphor.

Particles of each of the phosphors that has been obtained in the above-described method are grounded to powders and then sieved to obtain phosphor materials having a predetermined particle distribution.

Here, an explanation of the conventional

producing method of PDP will be given below.

First, display electrodes are formed on the front glass plate. The dielectric layer made of a dielectric glass is formed so as to cover the display electrodes.

5 On the dielectric layer, the protection layer is formed made of MgO. Then, the address electrodes are formed on the back glass plate. On the address electrodes, the visible light reflective layer made of a dielectric glass is formed. On the address electrodes, glass partition  
10 walls are formed with a predetermined pitch.

In the spaces between the partition walls, phosphor pastes which each include the red, green, and blue phosphors are put, respectively to form the phosphor layer. The phosphor layer is calcinated at approximately  
15 500°C to remove the resin component and the like in the pastes (the phosphor calcination process).

After the phosphor calcination, a glass frit for sealing the apertures between the front and back glass plates is applied onto the outer edge of the back glass  
20 plate, and the back glass plate is calcinated at 350°C (the glass calcination process for sealing).

Then, the front glass plate on which the display electrodes, the dielectric glass layer, and the protection layer have been formed in order and the back  
25 glass plate are positioned so as to face each other. In this case, the front and back glass plates are positioned

so that the display electrodes and the address electrodes intersect orthogonally via the partition walls. Then, the front and back glass plates are calcinated at 450°C to seal the front and back glass plates along the outer edges with sealing glass (the sealing process).

After the sealing process, while the panel is heated to a predetermined temperature (approximately 350°C), the air is exhausted from the panel (the exhaust process). After the exhaust process, the panel is filled with the discharge gas at a predetermined pressure.

In the above-described producing method of PDP, the light emitting properties gradually deteriorate after panel production, in the aging process for stabilizing the discharge properties, and in the normal operation. This is problematic.

This is because impurities (gas components different from the discharge gas such as water vapor, oxygen, nitrogen, and carbon dioxide) in the internal spaces are not completely cleaned and remain in the internal spaces in the exhaust process.

#### DISCLOSURE OF THE INVENTION

It is accordingly the object of the present invention to provide a method of producing a gas discharge panel that efficiently exhausts gas in the vacuum pumping process, which is necessary to the panel

producing processes.

The above-mentioned object may be achieved by a method of producing a gas discharge panel that includes: an envelope forming step for forming an envelope by providing over a first plate a second plate so that the second plate faces a main surface of the first plate, on which partition walls for partitioning light emitting cells have been formed; a sealing step for sealing the envelope with a sealant along outer edges of the first and second plates; an exhaust step for exhausting gas from the envelope; and a filling step for filling the envelope with a discharge gas, wherein the exhaust step includes: a substep for evacuating the envelope; a substep for filling the envelope with a cleaning gas that includes as a constituent a gas that substantially causes no impurity in the discharge gas; and a substep for re-evacuating the envelope.

The above-mentioned object may be also achieved by a method of producing a gas discharge panel that includes: an envelope forming step for forming an envelope by providing over a first plate a second plate so that the second plate faces a main surface of the first plate, on which partition walls for partitioning light emitting cells have been formed; a sealing step for sealing the envelope with a sealant along outer edges of the first and second plates; an exhaust step for

exhausting gas from the envelope; and a filling step for  
filling the envelope with a discharge gas, wherein the  
exhaust step includes: a substep for evacuating the  
envelope; and a substep for exhausting gas from the  
5 envelope while a cleaning gas is circulated through the  
envelope, the cleaning gas including as a constituent a  
gas that substantially causes no impurity in the  
discharge gas.

Note that the "includes as a constituent a gas  
10 that substantially causes no impurity in the discharge  
gas" means that "the major constituent of the cleaning  
gas causes no impurities in the discharge gas".

Unlike the conventional method, gas is not only  
exhausted from the envelope as in the case of the  
15 conventional producing method. According to these  
producing methods, gas is exhausted from the envelope  
after the envelope is filled with the cleaning gas or  
while the cleaning gas is circulated through the  
envelope. As a result, the concentration of impurity gas  
20 in the envelope can be swiftly (in a short period of  
time) lowered compared with the conventional method.

Also, when the pressure in the envelope is set to  
be lower than the pressure outside of the envelope while  
the entire envelope or the sealed part is heated to a  
25 temperature that is no lower than the softening point or  
the melting point of the sealant at the sealing step in

the producing methods, the sealant hardens to seal the envelope while the first and second plates are evenly pressed from the outside due to the pressure difference between the inside and the outside of the envelope. As a result, the envelope is sealed so that the entire top ends of the partition walls almost come in contact with the plate that faces the partition walls. According to the conventional method, the pressures inside and outside of the envelope are not set to be different and only the outer edges are tightly held with clips, so that the central parts of the first and second plates of the envelope are not pressed. As a result, the entire or part of the top ends of the partition walls tends to be apart from the facing plate when the envelope is sealed.

Accordingly, it is easy to produce a PDP with rare vibration at the time of drive and with excellent display quality according to the methods described above.

Also, when the envelope is filled with the dry gas at the sealing step, heat deterioration of the phosphors can be prevented.

#### BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, advantages and features of the invention will become apparent from the following description thereof taken in conjunction with the accompanying drawings that illustrate a specific

embodiment of the invention. In the Drawings:

Fig. 1 is a perspective view showing the structure of an AC plasma display panel (PDP) according to the embodiments of the present invention;

5 Fig. 2 shows the structure of a display device that is the PDP equipped with a circuit block;

Fig. 3 is diagrammatic sketches of a sealing/exhausting device 50 used in a sealing process of the first embodiment;

10 Fig. 3(a) is an overhead cutaway view of the seal/exhaust device 50;

Fig. 3(b) is a vertical sectional view taken on line A-A' of Fig. 3(a);

15 Fig. 4 shows temperature and pressure profiles during sealing (practical example);

Fig. 5 shows temperature and pressure profiles in an vacuum pumping/filling process (practical example);

20 Fig. 6 shows temperature and pressure profiles during sealing and in the vacuum pumping/filling process (practical example);

Fig. 7 is a diagrammatic sketch of a sealing/exhausting device 70 used in a sealing process of the second embodiment; and

25 Fig. 8 is a perspective view showing the structure of a PDP according to a conventional example.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

A specific explanation of a producing method of a PDP according to the present invention will be given below with reference to figures.

5

[Overall Structure and Producing Method of PDP]

Fig. 1 is a perspective view showing the structure of an AC surface discharge type PDP according to the embodiments of the present invention. Fig. 2 shows the structure of a display device that is the PDP equipped with a circuit block.

10

In the PDP, pulsed voltage is applied between the electrodes for discharge in the discharge spaces. Along with the discharge, visible lights of different colors are generated on the side of the back panel. The visible lights is emitted through the front panel.

15

The PDP is composed of a front panel 10 and a back panel 20. The front panel 10 is formed by disposing a plurality of display electrodes 12 (scan electrodes 12a and sustain electrodes 12b), a dielectric layer 13, and a protection layer 14 on a front glass plate 11. On the other hand, the back panel 20 is formed by disposing a plurality of address electrodes 22 and dielectric layer 23 on a back glass plate 21. The front and back panels are positioned so that the scan and sustain electrodes 12a and 12b and the address electrodes 22 face to each

20

25



other at a distance.

The center of the PDP is an area for displaying an image. The space between the front and back panels 10 and 20 are separated by a plurality of partition walls 24 that run in parallel to form a plurality of discharge spaces 30. The discharge spaces 30 are filled with discharge gas. In each of the discharge spaces 30, a phosphor layer 25 is disposed on the back panel 20. Different color phosphor layers 25, i.e., red, green, and blue phosphor layers 25 are repeatedly arranged in this order.

The display electrodes 12 and the address electrodes 22 are disposed in parallel, respectively. The display electrodes 12 are disposed orthogonally to and the address electrodes 22 in parallel to the partition walls 24.

As a result, cells which each emit red, green, and blue lights are formed where the display electrodes 12 and the address electrodes 22 intersect in the panel.

The dielectric layer 13 covers the entire surface of the front glass plate 11 on which the display electrodes 12 are disposed. The dielectric layer 13 is made of a dielectric substance. Low melting point lead glass is generally used. Low melting point bismuth glass, or layers of low melting point lead glass and low melting point bismuth glass may be also used.

The protection layer 14 is a thin film made of magnesium oxide (MgO). The protection layer 14 covers the entire surface of the dielectric layer 13. Having the function of the visible light reflective layer, TiO<sub>2</sub> particles are blended in the dielectric layer 23. The partition walls 24 are made of a glass material and are disposed on the surface of the dielectric layer 23 of the back panel 20 in a protruding condition.

Meanwhile, the front and back panels 10 and 20 are sealed with a sealant along the outer edge of the PDP.

The entire top ends of the partition walls 24 approximately come in contact with or are joined to the front panel 10 with a bonding material.

Here, an example of a producing method of the above-described PDP will be described.

#### (Manufacturing Front Panel)

The display electrodes 12 are formed on the front glass electrode 11. The dielectric layer 13 is formed so as to cover the display electrodes 12 and the front glass electrode 11. Then, on the surface of the dielectric layer 13, the protection layer 14 made of MgO is formed in the vacuum evaporation method, the electron beam evaporation method, or the CVD (Chemically Vapor Deposition) method. In this manner, the front panel is

manufactured.

The display electrodes 12 are formed by applying a silver electrode paste on the front glass electrode in the screen printing method and calcinating the paste.

5 Also, silver electrodes may be formed after forming transparent electrodes with ITO (Indium Tin Oxide) or  $\text{SnO}_2$  (tin dioxide), or Cr-Cu-Cr electrodes may be formed in the photo photolithographic method.

10 The dielectric layer 13 can be formed by applying a paste including a lead glass material (the composition is 70wt% of lead oxide ( $\text{PbO}$ ), 15wt% of ( $\text{B}_2\text{O}_3$ ), and 15wt% of silicon oxide ( $\text{SiO}_2$ ), for instance) on the front glass plate 11 in the screen printing method and calcinating the paste.

15 (Manufacturing Back Panel)

On the back glass plate 21, the address electrodes 22 are formed in the screen printing method as in the case of the display electrodes 12.

20 Then, the dielectric layer 23 is formed by applying a glass material with which  $\text{TiO}_2$  particles have been blended on the back glass plate 21 in the screen printing method and calcinating the paste.

25 Next, the partition walls 24 are formed. The partition walls 24 are formed by applying a partition wall glass paste on the back glass plate 21 in the screen

printing method and calcinating the paste. The partition walls 24 can be also formed by applying a partition wall glass paste on the entire surface of the back glass plate 21 and removing the paste from the parts where the partition walls 24 are not formed in the sand blast method.

In the channels between the partition walls, the phosphor layers 25 are formed. Generally, the phosphor layers 25 are formed by applying the phosphor pastes each of which includes phosphor particles of a different color in the screen printing method and calcinating the applied phosphor pastes. The phosphor layers 25 may be formed by continuously spraying phosphor inks from a nozzle on the channels while the nozzle scans the channels and calcinating the phosphor inks in order to remove the solvents and binders included in the phosphor inks. In each of the phosphor inks, phosphor particles of a different color are dispersed in a mixture of a binder, a solvent, a dispersant, and the like. The phosphor inks are adjusted so as to have an appropriate viscosity.

The following is specific examples of the phosphor particles.

Blue phosphor:  $\text{BaMgAl}_{10}\text{O}_{17}:\text{Eu}^{2+}$

Green phosphor:  $\text{BaAl}_{12}\text{O}_{19}:\text{Mn}$  or  $\text{Zn}_2\text{SiO}_4:\text{Mn}$

Red phosphor:  $(\text{Y}_x\text{Gd}_{1-x})\text{BO}_3:\text{Eu}^{3+}$  or  $\text{YBO}_3:\text{Eu}^{3+}$

In the preferred embodiments of the present

invention, the height of the partition walls is set to be 0.06 to 0.15mm and the pitch between the partition walls is 0.13 to 0.36mm in line with the Video Graphics Array (VGA) and high-definition TV set of 40 inch class.

5

(Sealing Process, Vacuum Pumping Process, and Discharge Gas Filling Process)

Next, the front panel 10 and the back panel 20 are sealed.

10 In the sealing process, the front panel 10 is provided on the back panel 20 and a sealant is inserted between the front panel 10 and the back panel 20 along the outer edges to form an envelope. The apertures between the front panel 10 and the back panel 20 along the outer edges are sealed with the sealant. When  
15 necessary, a bonding material can be applied on the top of the partition walls of the back panel 20.

The sealant is a material that is softened by energy such as heat from outside. Generally, low-melting  
20 glass is used as the bonding material. In the sealing process, the sealant is softened by heat and then hardened.

Also, in the sealing process, the pressures inside and outside of the envelope are set to be  
25 different so as to evenly apply pressure to the front panel 10 and the back panel 20 from the outside. By

doing so, the entire top ends of the partition walls <sup>24</sup> come in contact with or come closer to the front panel 10 in the sealing.

5 After the sealing process, a high vacuum ( $1.3 \times 10^{-11}$  MPa, for instance) is produced in the internal space to exhaust air in order to expel impurity gas that has been absorbed in the inside of the envelope (vacuum pumping process).

10 Then, the envelope is filled with a discharge gas (He-Xe, Ne-Xe, and Ar-Xe inert gas, for instance) at a predetermined pressure (discharge gas filling process). By doing so, the PDP is produced.

15 Note that Xe constitutes approximately 5vol% of the discharge gas and the pressure for filling is set in the range of 0.067 to 0.11Mpa in the preferred embodiments of the present invention

When driven for display, the PDP is equipped with a circuit block as shown in Fig. 2.

20 Explanations of the sealing process, the vacuum pumping process, and the discharge gas filling process will be given below in the first to fourth embodiments.

(The First Embodiment)

25 Fig. 3 is diagrammatic sketches of a sealing/exhausting device 50 used in the sealing process

of the first embodiment. Fig. 3(a) is an overhead cutaway view of the sealing/exhausting device 50 and Fig. 3(b) is a vertical sectional view taken on line A-A' of Fig. 3(a).

5 In the sealing/exhausting device 50, the envelope 40, which is formed by providing the front panel 10 on the back panel 20, is enclosed. The sealing/exhausting device 50 also includes a heating furnace 51 for applying heat to the envelope 40, a gas introducing system 52 that is equipped outside of the heating furnace 51, and a suction exhaust system 53.

To the heating furnace 51, heat can be applied by a heater 54. The internal temperature can be set at a desired temperature.

15 The sealing process is performed using the sealing/exhausting device 50 as follows.

As shown in Fig. 3, ventilation slots 21a and 21b are opened in advance in the back panel 20 at the regions that are positioned outside of the display area. The ventilation slot 21a is opened at the upper right of the back panel 20, while the ventilation slot 21b is at the bottom left in Fig. 3(a).

20 A paste including a sealant is applied to at least one of the joining surfaces of the front panel 10 and the back panel 20 along the outer edges. Then, the paste is calcinated to form a sealant layer 41. Here, a

low-melting glass having a softening temperature lower<sup>r</sup> than the materials of the dielectric layer 23 and the partition wall 24 is used as the sealant. Note that the sealant is not limited to the low-melting glass. Metals  
5 can be used. In this case, the temperature for sealing is the temperature at which the metal melts. Accordingly, the sealing temperature is higher than the melting point.

A specific example of the low-melting glass is  
10 the mixture of 80wt% of a low-melting glass frit (the softening temperature is 370°C), 5wt% of an ethyl cellulose binder, and 15wt% of isoamyl acetate. By applying the mixture with a dispenser, the sealant layer 41 is formed.

15 Between the sealant layer 41 and the outermost partition walls, partition members 42 are disposed so as to halve the spaces between the sealant layer 41 and the partition walls 24. The material of the partition members 42 can be the same as the material of the sealant  
20 layer 41 and the partition walls 24. Due to the partition members, gas is effectively introduced into and exhausted from the discharge spaces between the partition walls 24. Note that the partition members 42 cannot be disposed.

25 Then, the front panel 10 is provided on the back panel 20 to form the housing 40 while it is checked that



the front and back panels 10 and 20 are properly positioned. The outer edge of the envelope 40 is tightly held with clips (not illustrated) so that the front and back panels 10 and 20 do not shift the positions.

5           The envelope 40 is set inside of the heating furnace 51. Then, the gas introducing system 52 is connected to the ventilation slot 21a of the envelope 40 via a connecting tube 55. On the other hand, the suction exhaust system 53 is connected to the ventilation slot  
10 21b of the envelope 40 via a connecting tube 56.

          The connecting tubes 55 and 56 are glass tubes that are fixed to the back panel 20 at the lower surface via bonding members 55a and 56a. The material of the bonding members 55a and 56a is the same as the material  
15 of the sealant layer 41. More specifically, a paste including the low-melting glass is applied to the back panel 20 with a dispenser. Then, the paste is dried and the connecting tubes 55 and 56 are tentatively fastened to the back panel 20 with clips. By doing so, as the  
20 sealant layer 41 is softened and hardened to seal the envelope, the bonding members 55a and 56a are also softened and hardened. As a result, the connecting tubes 55 and 56 are connected to the ventilation slots 21a and 21b and the apertures between the connecting tubes 55 and  
25 56 and the ventilation slots 21a and 21b are sealed.

          The gas introducing system 52 includes a gas bomb

52a and a pipe system 52b, which connects the gas bomb 52a to the connecting tube 55. In the midst of the pipe system 52b, an open/close valve 52c is disposed for adjusting the amount of gas to be introduced. The  
5 connecting tube 55 and the pipe system 52b are connected to each other with a chuck so as to ensure airtightness.

The suction exhaust system 53 includes a manifold 53a, a turbo-molecule pump 53b, a rotary pump 53c, and pipe systems 53d and 53e. The pipe system 53d connects  
10 the connecting tube 56 to the manifold 53a. On the other hand, the pipe system 53e connects the manifold 53a to the turbo-molecule pump 53b. In the midst of the pipe system 53e, an open/close valve 53f is disposed for adjusting the amount of gas sucked out by the turbo-  
15 molecule pump 53b. The connecting tube 56 and the pipe system 53d are connected to each other with a chuck so as to ensure airtightness.

Note that the front panel 10 is provided on the back panel 20 in the present embodiment. However, the  
20 back panel 20 may be provided on the front panel 10 instead. Also, as long as the front and back panels 10 and 20 are held together so as not to shift the positions, the envelope 40 can be vertically set in the heating furnace.

25 The heating furnace 51 is heated to the sealing temperature that is slightly higher than the softening

temperature of the sealant (for instance, 450°C). Then,  
the heating furnace 51 is kept at the sealing temperature  
for a certain period of time and the temperature is  
lowered to a temperature that is no higher than the  
softening temperature. By doing so, the apertures  
between the front and back panels 10 and 20 are sealed.  
In the sealing, gas is being exhausted from the envelope  
40 by the turbo-molecule pump 53b. Note that when the  
turbo-molecule pump 53b is actuated, the rotary pump 53c  
is simultaneously actuated to lower the back pressure in  
the turbo-molecule pump 53b. The condition for sealing  
is determined by the compatibility between the material  
of the glass plates and the sealant. When the low  
melting point glass is used, the sealing condition is  
approximately 10 to 20 minutes around 450°C.

It is preferable to start the exhaust after the  
temperature in the heating furnace 51 reaches the  
softening temperature of the sealant. Before the  
temperature reaches the softening temperature, the  
airtightness of the outer edges of the front and back  
panels 10 and 20 is not high enough to produce a high  
vacuum in the envelope 40 even if gas is exhausted from  
the envelope 40. On the other hand, after the sealant is  
softened, the apertures between the front and back panels  
10 and 20 along the outer edges are sealed. Also, the  
bonding member 55a is softened to seal the apertures

between the connecting tube 55 and the ventilation slot<sup>5</sup> 21a. As a result, when the gas is exhausted from the envelope 40, the pressure is reduced to produce a high vacuum (approximately  $1.33 \times 10^{-4}$  MPa, i.e., approximately several Torr).

By exhausting gas from the envelope 40 as has been described, pressure is evenly applied to the front and back panels 10 and 20 from the outside. The degree of suction and exhaust by the suction exhaust system 53 is enough when the sealant is pressed to shrink due to the difference between the pressures in the envelope 40 and in the heating furnace and the front and back panels come to closer to each other so that the front panel touches the partition walls. For this reason, the suction and exhaust is slightly performed (for instance, approximately 0.08 MPa).

When pressure is evenly applied to the front and back panels 10 and 20 from the outside, the front panel 10 comes into contact with the top ends of the partition walls on the back panel 20 as shown in Fig. 3. When the temperature is lowered in this state, the temperature of the sealant becomes lower than the softening temperature and the sealant hardens to seal the envelope 40. As a result, the front panel 10 and the entire top ends of the partition walls are kept in absolute contact in the sealed envelope 40.

Note that the temperature is increased not at one stroke to the sealing temperature that is slightly higher than the softening temperature of the sealant in the sealing process. The temperature is kept at lower than the sealing temperature for a certain period of time, for instance, at around 350°C for 30 minutes, to burn out the binder material. This is effective at preventing the phosphor from deteriorating.

When the envelope 40 is sealed as has been described, the next processing advances to the vacuum pumping process.

In the vacuum pumping process, the inside of the heating furnace 51 is heated (baked) at a temperature (exhaust baking temperature) that is lower than the softening temperature of the sealant layer. In this heating, the open/close valve 53f is opened at an appropriate degree, and the turbo-molecule pump 53b and the rotary pump 53c are actuated so as to evacuate the envelope 40. Then, the discharge gas is introduced into the envelope 40 from the gas introducing system 52 with a predetermined pressure (for instance, 0.05MPa). It is preferable to keep the pressure for a predetermined period of time (5 to 10 minutes) after the envelope 40 is filled with the discharge gas. This is because it takes a certain period of time to reach the equilibrium pressure since the conductance between the partition

walls in the envelope is small.

Note that it is preferable to perform the vacuum pumping process at the baking temperature as has been described since the impurity that has been absorbed into the interior wall of the envelope 40 tends to fill the discharge space in gaseous form. In this situation, the impurity can be expelled from the envelope more swiftly. For this reason, the evacuation is generally performed at the exhaust baking temperature. The evacuation, however, is not limited to this case. Merely the evacuation can be performed.

Also, the exhaust baking temperature is lower than the softening temperature of the sealant. When a metal is used as the sealant, the softening temperature is lower than the melting point of the metal. Here, the exhaust baking temperature is a temperature that is effective at removing the absorbed water that has been absorbed into the interior wall of the envelope 40 (for instance, around 350°C).

The vacuum pumping process can start after the temperature of the envelope 40 is lowered to the room temperature. It is preferable, however, to start the vacuum pumping process when the sealing temperature in the sealing process is lowered to the exhaust baking temperature. This is because the manufacturing process can be shortened since the period of time to re-increase

the lowered temperature to the exhaust baking temperature is saved.

Then, the discharge gas introduction from the gas introducing system 52 is stopped and the discharge gas is sucked out from the envelope with the suction exhaust system 53 to re-establish a vacuum state in the envelope 40 again.

Usually, it is enough to perform a series of processes of vacuum pumping, discharge gas introduction, and vacuum pumping only once. When the series of processes is repeated, however, the impurity gas concentration is further lowered in the envelope 40.

Here, the gas introduced into the envelope 40 is not limited to discharge gas. Any kind of gas can be used as long as the gas is not any impurity gas for the discharge gas. Not clearly defined, the impurity is a kind of gas that lowers the intensity. Also, it is preferable that the gas to be introduced is a dry gas since the phosphor is prevented from deteriorating.

Here, the dry gas is a gas that has a partial pressure of water vapor lower than the ordinary gas. For instance, the partial pressure of water vapor (dew point) is no higher than 0.0027MPa (22°C).

The pressure that is to be introduced into the envelope 40 after evacuation can be from around  $1.33 \times 10^{-4}$  MPa (several Torr) to the maximum pressure with which

the envelope 40 is not broken. It is preferable that the pressure is lower than the atmospheric pressure.

The next process is the discharge gas filling process. In the discharge gas filling process, the discharge gas is supplied to the internal space of the envelope 40 by the gas introducing system 52 so as to have a predetermined pressure for filling (for instance, 0.067MPa). Then, the connecting tubes 55 and 56 are molten with a burner or a heater where the connecting tubes 55 and 56 are fixed to the back panel 20 to be sealed off (chipped off). As a result, the ventilation slots 21a and 21b are sealed.

#### [Effects of Producing Method of the First Embodiment]

When the pressure is set to be the same inside and outside of the envelope 40 and the envelope 40 is tightly held along the outer edge as in the case of the conventional producing method, pressure is not applied to the central parts of the front and panel of the envelope 40. As a result, a part or the entire part of the top ends of the partition walls on the back panel 20 tends not to come in contact with the front panel 10 when the envelope 40 is sealed. On the other hand, the sealant layer 41 is hardened to seal the envelope 40 while pressure is evenly applied to the front and back panels 10 and 20 from the outside as has been described in the



present embodiment. As a result, the front panel 10 almost comes into contact with the top ends of the partition walls when the envelope 40 is sealed.

Accordingly, it is easy to produce a PDP with rare vibration at the time of drive and with excellent display quality according to the producing method of the present embodiment.

In order to obtain these effects, it is at least necessary to actuate the suction exhaust system so as to set the pressures inside and outside of the envelope to be different when the softened sealant layer 41 is hardened. It is not necessary, however, to successively actuate the suction exhaust system 53 from the start to the end of the sealing process. For instance, when the suction exhaust system 53 starts to be actuated after the sealant layer 41 is softened, the effects due to the pressure difference between the inside and outside of the front and back panels 10 and 20 can be sufficiently obtained.

Also, as a result of the vacuum pumping process, the impurity gas concentration can be swiftly lowered.

This can be a result of 1) the effect of diluting impurity gas by filling the envelope with a large amount of discharge gas, 2) the effect of exhausting residual impurity gas from the envelope 40 by the viscous flow at the time of the gas filling and gas re-exhausting, 3) the

effect of removing absorbed gas by collision of discharge gas molecules with the internal wall of the envelope 40 such as the phosphors and the protection layer, and the like. According to the third effect, it is preferable to use a gas that has been heated as the discharge gas (cleaning gas) to be introduced into the envelope in the vacuum pumping process.

After the envelope 40 is evacuated while the temperature is kept at the exhaust baking temperature, the residual gas in the discharge space surrounded by the partition walls is not sufficiently exhausted from the envelope 40. For instance, suppose that the height of the partition walls in the envelope 40 is  $120\mu\text{m}$ , the pitch between the partition walls is  $200\mu\text{m}$ , the diameter of the slot for exhaust is approximately 2mm, the internal diameter of the connecting tube 56 is approximately 2mm, and the length of the connecting tube 56 is approximately 90mm. In this case, when the gas is exhausted at the exhaust baking temperature of  $350^{\circ}\text{C}$ , the pressure inside of the envelope 40 is 10 to 20 times the pressure inside of the manifold 53a even if the pressure inside of the manifold 53a is approximately  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$  MPa.

Of course, when the period of time for baking is lengthened, the amount of water and impurity gas that have been absorbed into the interior wall of the envelope

40 is reduced. The manufacturing cost is instead raised.

In the vacuum pumping process that has been described, after filled with the discharge gas, the envelope 40 is evacuated again. The impurity gas can be removed more swiftly according to the method described below.

While the envelope 40 is being filled with the discharge gas introduced by the gas introducing system 52, the discharge gas is exhausted from the envelope 40 with the suction exhaust system 53. The flow of the discharge gas is shown by large arrows in Fig. 3(a). B doing so, the discharge gas flows in the envelope 40, so that the impurity gas can be removed more efficiently. Especially, the impurity gas in the discharge space apart from the exhaust hole (the ventilation slot 21b) is effectively exhausted from the innermost part in the envelope 40.

In this case, it is possible to fill the envelope 40 with the discharge gas without evacuating the envelope 40 before the filling process.

#### (The First Practical Example)

A specific explanation of the first practical example of the PDP producing method in which each of the processes is performed according to the first preferred embodiment will be given below.

Fig. 4 shows temperature and pressure profiles during sealing. Fig. 5 shows temperature and pressure profiles in an vacuum pumping/filling process. In the first practical example, the PDP is manufactured according to each of the profiles. Note that the dotted line in Figs. 4 and 5 shows the temperature of the envelope 40 while the solid line the pressure change in the manifold 53a.

The sealing process will be explained first. The temperature is increased to the sealing temperature, 450°C in two to three hours, and the sealing temperature is kept for about 20 minutes. Meanwhile, when the temperature reaches 450°C, the pressure in the manifold 53a is lowered to around 0.05MPa and the suction exhaust system is stopped and remains stopped.

Then, while the lowered pressure is kept, the temperature is decreased to the room temperature in two to three hours.

At this stage, the front and back panels have been sealed.

Next, as shown in Fig. 5, the evacuation is continued and heating is started after the pressure in the manifold 53a becomes around  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$  MPa. The temperature is increased to the exhaust baking temperature (350°C) in two to three hours. When the temperature reaches the exhaust baking temperature, the

evacuation is started again to exhaust the gas that has<sup>h,n</sup> circulated into the manifold during the temperature increase. When the evacuation is resumed, the pressure in the manifold 53a rises as indicated by an arrow 60 in Fig. 5 due to the gas removed from the interior walls of the connecting tube 56 and the envelope 40. At the start of the evacuation, however, the pressure begins lowering.

Then, when the pressure in the manifold 53a reaches around  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$  MPa, the suction exhaust system 53 stops and the gas introducing system 52 is actuated. The envelope 40 is filled with the discharge gas with around 0.05 MPa of pressure and the pressure is kept for five to 10 minutes.

After that, in the course of cooling, gas starts to be evacuated from the envelope 40. After the pressure reaches around  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$ , the gas introducing system 52 fills the envelope 40 with the discharge gas with 0.067 MPa of pressure.

In the conventional vacuum pumping process, it takes around two hours to lower the pressure in the envelope to  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$ . On the other hand, pressure can be lowered more swiftly in the vacuum pumping process of the first practical example. More specifically, it takes about one hour.

Here, the pressure can be lowered in a short period of time by increasing the driving force of the

pump system of the suction exhaust system and evacuating the envelope more powerfully. In this case, however, the phosphors in the envelope come off the phosphor layers, for instance, leading to panel property deterioration.

5 For this reason, the manifold is disposed as has been described to weaken the force of suction to evacuate the envelope. As a result, it takes a relatively long period of time to lower the pressure in the envelope in the conventional vacuum pumping process.

10 For the PDP that has been produced according to the above-mentioned method, lifting rarely occurs in the outer regions. Also, the discharge properties are even compared with the conventional method in which pressure is applied only with clips. The level of noise from the  
15 outer regions is reduced by approximately several to 10db. The voltage at the start of discharge decreases by approximately 5 to 10V. Furthermore, the discharge current decreases by approximately several to 10% and the effectiveness improves by around 10%.

20 (The Second Practical Example)

An explanation of the second practical example of the PDP producing method in which each of the processes is performed according to the first preferred embodiment  
25 will be given below.

Fig. 6 shows temperature and pressure profiles

during the sealing and in the vacuum pumping/filling process. In the second practical example, the PDP is produced according to the profiles. Note that dotted line in Fig. 6 shows the temperature of the envelope 40 while the solid line the pressure change in the manifold of the suction exhaust system connected to the envelope 40.

The sealing process will be explained first. The temperature is increased to the sealing temperature, 450°C in two to three hours, and the sealing temperature is kept for about 20 minutes. Meanwhile, when the temperature reaches 450°C, the pressure in the manifold 53a is lowered to around 0.05MPa and the suction exhaust system is stopped and remains stopped.

Then, while the lowered pressure is kept, the temperature is decreased to the exhaust baking temperature (350°C) in 30 minutes.

At this stage, the front and back panels have been sealed. When the pressure in the manifold 53a is monitored as the temperature is decreased, defective sealing can be detected and dealt with in the early stage of the producing process to help lower the cost.

Next, after the temperature is decreased to the exhaust baking temperature, the evacuation is continued to lower the pressure in the manifold 53a to  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$  MPa. Then, the suction exhaust system 53 is

stopped and the gas introducing system 52 is actuated to fill the envelope 40 with the discharge gas with 1.15MPa of pressure. The pressure is kept for five to 10 minutes.

5           After that, in the course of cooling, gas starts to be evacuated from the envelope 40. After the pressure reaches around  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$ , the gas introducing system 52 fills the envelope 40 with the discharge gas with 0.067MPa of pressure.

10           In the conventional vacuum pumping process, it takes around two hours to lower the pressure in the envelope to  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$ . On the other hand, pressure can be lowered more swiftly in the vacuum pumping process according to the first embodiment. More specifically, it takes about one hour.

15           For the PDP that has been produced according to the above-mentioned method, lifting rarely occurs in the outer regions. Also, the discharge properties are even compared with the conventional method in which pressure is applied only with clips. The level of noise from the outer regions is reduced by approximately several to 10db. The voltage at the start of discharge decreases by approximately 5 to 10V. Furthermore, the discharge current decreases by approximately several to 10% and the effectiveness improves by around 10%.

25           Compared with the first practical example, the



producing method in the second practical example is effective at shortening the period of time from the sealing to the cooling of the envelope 40 and the period of time for heating from the room temperature to the exhaust baking temperature. Also, the phosphor deteriorates less than the first practical example by several percent or so. The quality is slightly better than the first practical example.

#### 10 (The Second Embodiment)

The second embodiment is different from the first embodiment in the method in the vacuum pumping process.

Fig. 7 is a diagrammatic sketch of a sealing/exhausting device 70 used in the sealing process of the second embodiment. Fig. 7 corresponds to Fig. 3(b).

The sealing/exhausting device 70 encloses the envelope 40, which is formed by providing the front panel 10 on the back panel 20. Also, the sealing/exhausting device 70 includes a heating furnace 71 for heating the envelope 40 and a gas introducing/suction exhaust system 72 that is provided outside of the heating furnace 71.

To the back panel 20, a connecting tube 73 and a getter tube 74 are tentatively fastened via bonding members 73a and 74a so as to connect the ventilation slots 21a and 21b to the internal space, respectively as

in the case of the first embodiment.

The connecting tube 73 is a glass tube that connects to the back panel 20 with an open end. The getter tube 74 is a glass tube that connects to the back panel 20 with a sealed end. At the end of the getter tube 74 corresponding to the exit of the ventilation slot 21b in the back panel 20, a getter enclosing space 74b is formed for enclosing a getter.

The gas introducing/suction exhaust system 72 includes a manifold 72a, a turbo-molecule pump 72b, a rotary pump 72c, a gas bomb 72d, a pipe system 72e, and a branch connection system 72f. The gas bomb 72d is filled with the discharge gas. The pipe system 72e connects the connecting tube 73 to the manifold 72a. The branch connection system 72f connects the manifold 72a to the turbo-molecule pump 72b and the gas bomb 72d. In the branch connection system 72f, a connection system 72f1 from the manifold 72a branches into connection systems 72f2 and 72f3 via a channel selection valve 72g. The connection systems 72f2 and 72f3 are connected to the turbo-molecule pump 72b and the gas bomb 72d, respectively. In the midst of the connection systems 72f2 and 72f3, open/close valves 72h and 72i are disposed. While the open/close valve 72h adjusts the amount of gas sucked out by the turbo-molecule pump, the 72i open/close valve adjusts the amount of flow of

discharge gas. The connecting tube 73 and the pipe system 72e are connected to each other with a chuck so as to ensure airtightness. The channel selection valve 72g selects the connection system 72f2 when the turbo-  
5 molecule pump 72b is actuated. On the other hand, the connection system 72f3 is selected when the discharge gas is introduced into the envelope 40 from the gas bomb 72d.

Then, the temperature in the heating furnace 71 is increased to a sealing temperature (for instance,  
10 450°C) that is slightly higher than the softening temperature of the sealant by a heater 75. After kept at the sealing temperature for a certain period of time, the temperature is decreased lower than the softening temperature. By doing so, the apertures between the  
15 front and back panels 10 and 20 are sealed. In the sealing, the envelope 40 is evacuated by the turbo-molecule pump 72b from the inside. The condition for sealing is determined by the compatibility between the material of the glass plates and the sealant. When the  
20 low melting point glass is used, the sealing condition is approximately 10 to 20 minutes around 450°C.

It is preferable to start the exhaust after the temperature in the heating furnace 71 reaches the softening temperature of the sealant. Before the  
25 temperature reaches the softening temperature, the airtightness of the outer edges of the front and back

panels 10 and 20 is not high enough to produce a high vacuum in the envelope 40 even if gas is exhausted from the envelope 40. On the other hand, after the sealant is softened, the apertures between the front and back panels 10 and 20 along the outer edges are sealed. Also, the sealant layer 41 is softened to seal the apertures between the connecting tube 72 and the ventilation slot 21a. As a result, when the gas is exhausted from the envelope 40, the pressure is reduced to produce a high vacuum (approximately  $1.33 \times 10^{-4}$  MPa, i.e., approximately several Torr).

By exhausting gas from the envelope 40 as has been described, pressure is evenly applied to the front and back panels 10 and 20 from the outside. The degree of suction and exhaust is enough when the sealant is pressed to shrink due to the difference between the pressures in the envelope 40 and in the heating furnace and the front and back panels come to closer to each other so that the front panel touches the partition walls. For this reason, the suction and exhaust is slightly performed (for instance, approximately 0.08 MPa).

When pressure is evenly applied to the front and back panels 10 and 20 from the outside, the front panel 10 comes into contact with the top ends of the partition walls on the back panel 20 as has been described. When the temperature is lowered in this state, the temperature

of the sealant becomes lower than the softening  
temperature and the sealant hardens to seal the envelope  
40. As a result, the front panel 10 and the entire top  
ends of the partition walls are kept in absolute contact  
5 in the sealed envelope 40.

Next, after the temperature is lowered to the  
room temperature, an end 74c of the getter tube 74 is  
broken to insert getter 76. The amount of the getter 76  
corresponds to the size of the internal space of the  
10 envelope 40. Then, the end 74c is sealed off to enclose  
the getter 76 into the getter enclosing space 74b. The  
getter 76 can be a substance the surface of which is  
activated by heating to irreversibly, chemically absorb  
the impurity gas. In this case, it is preferable to use  
15 a substance that is chemically activated at the exhaust  
baking temperature later in the vacuum pumping process.

Then, after a vacuum state is re-established in  
the envelope 40, heating (baking) is started when the  
temperature in the heating furnace 71 is lower than the  
20 softening temperature of the sealant layer (at the  
exhaust baking temperature).

Also, the exhaust baking temperature is lower  
than the softening temperature of the sealant. When a  
metal is used as the sealant, the softening temperature  
25 is lower than the melting point of the metal. Here, the  
exhaust baking temperature is a temperature that

activates the getter 76 and is effective at removing the absorbed water that has been absorbed into the interior wall of the envelope 40 (for instance, around 350°C).

When the temperature reaches the temperature for activating the getter 76 during the temperature increase to the exhaust baking temperature, water and impurity gas such as carbon dioxide, nitrogen, oxygen, and so on are absorbed to the surface of the particle of the getter 76. The absorbed water and impurity gas is taken in the particle pores. This is because of the pressure gradient (gas concentration gradient) between the internal space of the envelope 40 and the getter enclosing space 74b, into which the getter 76 is enclosed, as a result that the impurity gas is taken in the getter 76.

Then, while the temperature is kept at the exhaust baking temperature, the open/close valve 72h is opened to an appropriate degree and the turbo-molecule pump 72b and the rotary pump 72c are activated to further evacuate the envelope 40. After that, the connection system 72f3 is selected with the channel selection valve 72g and the open/close valve 72i is opened to introduce the discharge gas into the envelope 40 with a predetermine pressure (for instance, 0.05MPa). It is more preferable to keep the pressure for a predetermined period of time (five to 10 minutes) after the envelope 40 is filled with the discharge gas. This is because it

takes a certain period of time to reach the equilibrium pressure since the conductance between the partition walls in the envelope 40 is small.

Then, the discharge gas introduction is stopped and the discharge gas is sucked out from the envelope to re-establish a vacuum state in the envelope 40 again.

Usually, it is enough to perform a series of processes of vacuum pumping, discharge gas introduction, and vacuum pumping only once. When the series of processes is repeated, however, the impurity gas concentration is further lowered in the envelope 40.

Here, the gas introduced into the envelope 40 is not limited to discharge gas. Any kind of gas can be used as long as the gas is not impurity for discharge gas. Also, it is preferable that the gas to be introduced is a dry gas since the phosphor is prevented from deteriorating.

The pressure that is to be introduced into the envelope 40 after evacuation can be from around  $1.33 \times 10^{-4}$  MPa (several Torr) to the maximum pressure with which the envelope 40 is not broken. It is preferable that the pressure is lower than the atmospheric pressure.

The next process is the discharge gas filling process. In the discharge gas filling process, the discharge gas is supplied to the internal space of the envelope 40 so as to have a predetermined pressure for

filling (for instance, 0.067MPa). Then, the connecting tubes 73 and the getter tube 74 are molten with a burner or a heater where the connecting tubes 55 and 56 are fixed to the back panel 20 to be sealed off (chipped off). As a result, the ventilation slots 21a and 21b are sealed.

[Effects of Producing Method of the Second Embodiment]

When the pressure is set to be the same inside and outside of the envelope 40 and the envelope 40 is tightly held along the outer edge as in the case of the conventional producing method, pressure is not applied to the central parts of the front and back panels of the envelope 40. As a result, a part or the entire part of the top ends of the partition walls on the back panel 20 tends not to come in contact with the front panel 10 when the envelope 40 is sealed. On the other hand, the sealant layer 41 is hardened to seal the envelope 40 while pressure is evenly applied to the front and back panels 10 and 20 from the outside as has been described in the present embodiment. As a result, the front panel 10 almost comes into contact with the top ends of the partition walls when the envelope 40 is sealed.

Accordingly, it is easy to produce a PDP with rare vibration at the time of drive and with excellent display quality according to the producing method of the



present embodiment.

In order to obtain these effects, it is at least necessary to actuate the suction exhaust system so as to set the pressures inside and outside of the envelope to be different when the softened sealant layer 41 is hardened. It is not necessary, however, to successively evacuate the envelope 40 from the start to the end of the sealing process. For instance, when the envelope 40 starts to be evacuated after the sealant layer 41 is softened, the effects due to the pressure difference between the inside and outside of the front and back panels 10 and 20 can be sufficiently obtained.

Also, as a result of the vacuum pumping process, the impurity gas concentration can be swiftly lowered.

This can be a result of 1) the effect of diluting impurity gas by filling the envelope with a large amount of discharge gas, 2) the effect of exhausting residual impurity gas from the envelope 40 by the viscous flow at the time of the gas filling and gas re-exhausting, 3) the effect of removing absorbed gas by collision of discharge gas molecules with the internal wall of the envelope 40 such as the phosphors and the protection layer, and the like. According to the third effect, it is preferable to use a gas that has been heated as the discharge gas (cleaning gas) to be introduced into the envelope in the vacuum pumping process.

Also, in the present embodiment, the process for removing impurity gas in the envelope with the getter is included in the step to increase the temperature to the exhaust baking temperature. As a result, impurity gas can be removed more swiftly and the impurity gas concentration can be further lowered compared with the producing method in the first embodiment, in which only the series of processes of vacuum pumping, discharge gas introduction, and vacuum pumping is performed.

#### (The Third Practical Example)

A specific explanation of the third practical example of the PDP producing method in which each of the processes is performed according to the first preferred embodiment will be given below.

In the third practical example, the PDP is manufactured according to each of the profiles shown in Figs. 4 and 5. The getter 76 is inserted into the getter tube 74 when the sealing has been performed and the temperature has been lowered to the room temperature. As the getter, vanadium, titanium, and iron alloy particles that are activated at 280°C are used.

In the conventional vacuum pumping process, it takes around two hours to lower the pressure in the envelope to  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$ . On the other hand, pressure can be lowered in around one hour in the vacuum

pumping process of the third practical example.

For the PDP that has been produced according to the above-mentioned method, lifting rarely occurs in the outer regions. Also, the discharge properties are even compared with the conventional method in which pressure is applied only with clips. The level of noise from the outer regions is reduced by approximately several to 10db. The voltage at the start of discharge decreases by approximately 5 to 10V. Furthermore, the discharge current decreases by approximately several to 10% and the effectiveness improves by around 10%.

Compared with the first practical example, properties slightly less deteriorates after an aging process (i.e., a process for stabilizing the panel properties after the discharge gas filling process) in the producing method in the third practical example. Also, the producing method is more effective by several percent.

## (The Third Embodiment)

The third embodiment is different from the first embodiment in the method in the sealing process.

First, the temperature in the heating furnace is increased to the sealing temperature that is slightly higher than the softening temperature of the sealant (for instance, 450°C). After kept at the sealing temperature

for a predetermined period of time, the temperature is decreased lower than the softening temperature. By doing so, the apertures between the front and back panels 10 and 20 are sealed. While the temperature is increased to the sealing temperature, the gas introducing system is actuated to introduce dry gas into the envelope 40. Note that dried discharge gas with which the gas bomb 52a is charged is used as the dry gas in the third embodiment. Also, dry air, dry nitrogen gas, dry argon gas, dry neon gas (all referred to as noble gas) can be used as the dry gas. When the temperature reaches the sealing temperature, the sealant is softened to ensure the airtightness of the envelope 40. As a result, the internal pressure of the envelope 40 is increased. When the internal pressure increase is monitored, the introduction of the discharge gas is stopped.

Note that the amount of dry gas is limited so that the glass plates of the envelope 40 are not broken due to sharp pressure increase even if the dry gas flows into the envelope 40 when the sealant is softened to seal the envelope 40.

As has been described, the dry gas is composite through the envelope 40 until the temperature reaches the sealing temperature. As a result, when the envelope 40 has been sealed by softened sealant, the envelope 40 is filled with the dry gas. Then, the temperature is kept

at the sealing temperature for a predetermined period of time. The condition for sealing is determined by the compatibility between the material of the glass plates and the sealant. When the low melting point glass is used, the sealing condition is approximately 10 to 20 minutes around 450°C.

In this way, the envelope 40 is sealed while the envelope 40 is filled with the dry gas. By doing so, heat deterioration of the phosphors is prevented.

Furthermore, the temperature is kept at the sealing temperature while the envelope is filled with the dry gas. At the same time, the sealing is performed while the envelope is evacuated with the turbo-molecule pump 53b. Note that when the turbo-molecule pump 53b is activated, the rotary pump 53c is also activated to lower the back pressure in the turbo-molecule pump 53b.

It is preferable to start the exhaust after the temperature in the heating furnace 51 reaches the softening temperature of the sealant.. Before the temperature reaches the softening temperature, the airtightness of the outer edges of the front and back panels 10 and 20 is not high enough to produce a high vacuum in the envelope 40 even if gas is exhausted from the envelope 40. On the other hand, after the sealant is softened, the apertures between the front and back panels 10 and 20 along the outer edges are sealed. Also, the

bonding member 56a is softened to seal the apertures between the connecting tube 56 and the ventilation slot 21b. As a result, when the gas is exhausted from the envelope 40, the pressure is reduced to produce a high vacuum (approximately  $1.33 \times 10^{-4}$  MPa, i.e., approximately several Torr).

By exhausting gas from the envelope 40 as has been described, pressure is evenly applied to the front and back panels 10 and 20 from the outside. The degree of suction and exhaust is enough when the sealant is pressed to shrink due to the difference between the pressures in the envelope 40 and in the heating furnace and the front and back panels come to closer to each other so that the front panel touches the partition walls. For this reason, the suction and exhaust is slightly performed (for instance, approximately 0.08 MPa).

When pressure is evenly applied to the front and back panels 10 and 20 from the outside, the front panel 10 comes into contact with the top ends of the partition walls on the back panel 20 as shown in Fig. 3. When the temperature is lowered in this state, the temperature of the sealant becomes lower than the softening temperature and the sealant hardens to seal the envelope 40. As a result, the front panel 10 and the entire top ends of the partition walls are kept in absolute contact in the sealed envelope 40.

Note that the temperature is increased not at one stroke to the sealing temperature that is slightly higher than the softening temperature of the sealant in the sealing process. The temperature is kept at lower than the sealing temperature for a certain period of time, for instance, at around 350°C for 30 minutes, to burn out the binder material. This is effective at preventing the phosphor from deteriorating.

After the sealing process, the processing advances to the vacuum pumping process, the sealing process, and the discharge gas filling process to produce the PDP as in the case of the first embodiment.

#### (The Fourth Practical Example)

A specific explanation of the fourth practical example of the PDP producing method in which each of the processes is performed according to the third preferred embodiment will be given below.

In the fourth practical example, the PDP is manufactured according to each of the profiles shown in Figs. 4 and 5.

The sealing process will be explained first. The temperature is increased to the sealing temperature, 450°C in two to three hours, and the sealing temperature is kept for about 20 minutes. Meanwhile, the dry gas is composite through the envelope 40 by activating the gas

introducing system until the temperature reaches the sealing temperature.

Then, when the temperature reaches 450°C, the gas introducing system is stopped and the pressure in the manifold is lowered to and kept around 0.05MPa.

Next, while the lowered pressure is kept, the temperature is decreased to the room temperature in two to three hours.

At this stage, the front and back panels have been sealed. When the pressure in the manifold is monitored as the temperature is decreased, defective sealing can be detected and dealt with in the early stage of the producing process to help lower the cost. The pressure in the manifold gradually drops when the sealing is normally performed. If the sealing is not normally performed, however, gas is leaked into the heating furnace, so that the pressure drops at a relatively high speed.

Next, as shown in Fig. 5, the evacuation is continued and heating is started after the pressure in the manifold 53a becomes around  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$  MPa. The temperature is increased to the exhaust baking temperature (350°C) in two to three hours. When the temperature reaches the exhaust baking temperature, the evacuation is started again to exhaust the gas that has flowed into the manifold during the temperature increase.



When the evacuation is resumed, the pressure in the manifold 53a rises as indicated by an arrow 60 in Fig. 5 due to the gas removed from the interior walls of the connecting tube and the envelope 40. At the start of the evacuation, however, the pressure begins lowering.

Then, when the pressure in the manifold 53a reaches around  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$  MPa, the suction exhaust system 53 stops and the gas introducing system 52 is actuated. The envelope 40 is filled with the discharge gas with around 0.05 MPa of pressure and the pressure is kept for five to 10 minutes.

After that, in the course of cooling, gas starts to be evacuated from the envelope 40. After the pressure reaches around  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$ , the gas introducing system 52 fills the envelope 40 with the discharge gas with 0.067 MPa of pressure.

In the conventional vacuum pumping process, it takes around two hours to lower the pressure in the envelope to  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$ . On the other hand, pressure can be lowered in about one hour in the vacuum pumping process of the fourth practical example.

For the PDP that has been produced according to the above-mentioned method, lifting rarely occurs in the outer regions. Also, the discharge properties are even compared with the conventional method in which pressure is applied only with clips. The level of noise from the

outer regions is reduced by approximately several to 10db. The voltage at the start of discharge decreases by approximately 5 to 10V. Furthermore, the discharge current decreases by approximately several to 10% and the effectiveness improves by around 10%.

Meanwhile, a comparative evaluation of the luminescence intensity (intensity/"y" chromaticity coordinate value) is performed on the phosphors of the PDP that has been sealed after dry gas is circulated as has been described and the PDP that has been sealed while the atmosphere is included in the PDP according to the conventional method. The comparative evaluation is performed by breaking the panel and irradiate Xe excimer lamp (with 173nm of wavelength). The luminescence intensity is improved by around 10% for the blue phosphor. Although the luminescence intensity is improved for all kinds of non-reactive dry gas, significantly improved for dry air.

#### (The Fifth Practical Example)

A specific explanation of the fifth practical example of the PDP producing method in which each of the processes is performed according to the third preferred embodiment will be given below.

In the fifth practical example, the PDP is manufactured according to each of the profiles shown in

Fig. 6.

The sealing process will be explained first. The temperature is increased to the sealing temperature, 450°C in two to three hours, and the sealing temperature is kept for about 20 minutes. Meanwhile, the dry gas is circulated through the envelope 40 by activating the gas introducing system until the temperature reaches the sealing temperature.

Then, when the temperature reaches 450°C, the gas introducing system is stopped and the pressure in the manifold is lowered to and kept around 0.05MPa.

Next, while the lowered pressure is kept, the temperature is decreased to the exhaust baking temperature (350°C) in around 30 minutes.

At this stage, the front and back panels have been sealed. When the pressure in the manifold is monitored as the temperature is decreased, defective sealing can be detected and dealt with in the early stage of the producing process to help lower the cost.. The pressure in the manifold gradually drops when the sealing is normally performed. If the sealing is not normally performed, however, gas is leaked into the heating furnace, so that the pressure drops at a relatively high speed.

Next, after the temperature is decreased to the exhaust baking temperature, the evacuation is continued

to lower the pressure in the manifold to  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$  MPa. Then, the suction exhaust system 53 is stopped and the gas introducing system 52 is actuated to fill the envelope 40 with the discharge gas with 1.15 MPa of pressure. The pressure is kept for five to 10 minutes.

After that, in the course of cooling, gas starts to be evacuated from the envelope 40. After the pressure reaches around  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$ , the gas introducing system fills the envelope 40 with the discharge gas with 0.067 MPa of pressure.

In the conventional vacuum pumping process, it takes around two hours to lower the pressure in the envelope to  $1.3 \times 10^{-11}$  to  $1.3 \times 10^{-10}$ . On the other hand, pressure can be lowered more swiftly in the vacuum pumping process according to the first embodiment. More specifically, it takes about one hour.

For the PDP that has been produced according to the above-mentioned method, lifting rarely occurs in the outer regions. Also, the discharge properties are even compared with the conventional method in which pressure is applied only with clips. The level of noise from the outer regions is reduced by approximately several to 10db. The voltage at the start of discharge decreases by approximately 5 to 10V. Furthermore, the discharge current decreases by approximately several to 10% and the

effectiveness improves by around 10%.

Compared with the fourth practical example, the producing method in the fifth practical example is effective at shortening the period of time from the sealing to the cooling of the envelope 40 and the period of time for heating from the room temperature to the exhaust baking temperature. Also, the phosphor deteriorates less than the first practical example by several percent or so. The quality is slightly better than the fourth practical example.

#### (The Fourth Embodiment)

The fourth embodiment is different from the second embodiment in the method in the sealing process.

First, the temperature in the heating furnace 71 is increased to the sealing temperature that is slightly higher than the softening temperature of the sealant (for instance, 450°C). After kept at the sealing temperature for a predetermined period of time, the temperature is decreased lower than the softening temperature. By doing so, the apertures between the front and back panels 10 and 20 are sealed. While the temperature is increased to the sealing temperature, the gas introducing system is actuated to introduce dry gas into the envelope 40. Note that dried discharge gas with which the gas bomb 72d is charged is used as the dry gas in the third embodiment.

Also, dry air, dry nitrogen gas, dry argon gas, dry neon<sup>n</sup> gas (all referred to as noble gas) can be used as the dry gas. When the temperature reaches the sealing temperature, the sealant is softened to ensure the airtightness of the envelope 40. As a result, the internal pressure of the envelope 40 is increased. When the internal pressure increase is monitored, the introduction of the discharge gas is stopped.

Note that the amount of dry gas is limited so that the glass plates of the envelope 40 are not broken due to sharp pressure increase even if the dry gas flows into the envelope 40 when the sealant is softened to seal the envelope 40.

As has been described, the dry gas is circulated through the envelope 40 until the temperature reaches the sealing temperature. As a result, when the envelope 40 has been sealed by softened sealant, the envelope 40 is filled with the dry gas. Then, the temperature is kept at the sealing temperature for a predetermined period of time. The condition for sealing is determined by the compatibility between the material of the glass plates and the sealant. When the low melting point glass is used, the sealing condition is approximately 10 to 20 minutes around 450°C.

In this way, the envelope 40 is sealed while the envelope 40 is filled with the dry gas. By doing so,

heat deterioration of the phosphors is prevented.

Furthermore, the temperature is kept at the sealing temperature while the envelope is filled with the dry gas. At the same time, the sealing is performed while the envelope is evacuated with the turbo-molecule pump 72b. Note that when the turbo-molecule pump 72b is activated, the rotary pump 72c is also activated to lower the back pressure in the turbo-molecule pump 72b.

It is preferable to start the exhaust after the temperature in the heating furnace 71 reaches the softening temperature of the sealant. Before the temperature reaches the softening temperature, the airtightness of the outer edges of the front and back panels 10 and 20 is not high enough to produce a high vacuum in the envelope 40 even if gas is exhausted from the envelope 40. On the other hand, after the sealant is softened, the apertures between the front and back panels 10 and 20 along the outer edges are sealed. Also, the bonding member 73a is softened to seal the apertures between the connecting tube 73 and the ventilation slot 21a. As a result, when the gas is exhausted from the envelope 40, the pressure is reduced to produce a high vacuum (approximately  $1.33 \times 10^{-4}$  MPa, i.e., approximately several Torr).

By exhausting gas from the envelope 40 as has been described, pressure is evenly applied to the front

and back panels 10 and 20 from the outside. The degree of suction and exhaust is enough when the sealant is pressed to shrink due to the difference between the pressures in the envelope 40 and in the heating furnace and the front and back panels come to closer to each other so that the front panel touches the partition walls. For this reason, the suction and exhaust is slightly performed (for instance, approximately 0.08MPa).

When pressure is evenly applied to the front and back panels 10 and 20 from the outside, the front panel 10 comes into contact with the top ends of the partition walls on the back panel 20 as shown in Fig. 3. When the temperature is lowered in this state, the temperature of the sealant becomes lower than the softening temperature and the sealant hardens to seal the envelope 40. As a result, the front panel 10 and the entire top ends of the partition walls are kept in absolute contact in the sealed envelope 40.

Note that the temperature is increased not at one stroke to the sealing temperature that is slightly higher than the softening temperature of the sealant in the sealing process. The temperature is kept at lower than the sealing temperature for a certain period of time, for instance, at around 350°C for 30 minutes, to burn out the binder material. This is effective at preventing the phosphor from deteriorating.



After the sealing process, the processing advances to the vacuum pumping process, the sealing process, and the discharge gas filling process to produce the PDP as in the case of the first embodiment.

5

(The Sixth Practical Example)

A specific explanation of the sixth practical example of the PDP producing method in which each of the processes is performed according to the fourth preferred embodiment will be given below.

10

In the sixth practical example, the PDP is manufactured according to the same temperature and pressure profiles as in the fourth practical example. The getter 76 is inserted into the getter tube 74 when the sealing has been performed and the temperature has been lowered to the room temperature. As the getter, vanadium, titanium, and iron alloy particles that are activated at 280°C are used.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
21

compared with the conventional method in which pressure is applied only with clips. The level of noise from the outer regions is reduced by approximately several to 10db. The voltage at the start of discharge decreases by approximately 5 to 10V. Furthermore, the discharge current decreases by approximately several to 10% and the effectiveness improves by around 10%.

Meanwhile, a comparative evaluation of the luminescence intensity (intensity/"y" chromaticity coordinate value) is performed on the phosphors of the PDP that has been sealed after dry gas is circulated as has been described and the PDP that has been sealed while the atmosphere is included in the PDP according to the conventional method. The comparative evaluation is performed by breaking the panel and irradiate Xe excimer lamp (with 173nm of wavelength). The luminescence intensity is improved by around 10% for the blue phosphor. Although the luminescence intensity is improved for all kinds of non-reactive dry gas, significantly improved for dry air.

Note that while the sealing process and the vacuum pumping process have been performed in the same apparatus in the first to fourth preferred embodiments, it is not the only case. The sealing process and the vacuum pumping process can be performed in different apparatuses.

Also, heat is not always applied to the envelope<sup>z</sup> as a whole in the sealing process. It is possible to selectively apply a heat source such as the laser beam to the part where the envelope is to be sealed so as to  
5 selectively apply heat to seal the envelope. In this case, the phosphors are not directly heated. As a result, it is assumed that the phosphors are rarely deteriorated by heat in the sealing process even if dry gas is not introduced into the discharge space.

10 As has been described, the present invention is a method of producing a gas discharge panel that includes: an envelope forming step for forming an envelope by providing over a first plate a second plate so that the second plate faces a main surface of the first plate, on  
15 which partition walls for partitioning light emitting cells have been formed; a sealing step for sealing the envelope with a sealant along outer edges of the first and second plates; an exhaust step for exhausting gas from the envelope; and a filling step for filling the  
20 envelope with a discharge gas, wherein the exhaust step includes: a substep for evacuating the envelope; a substep for filling the envelope with a cleaning gas that includes as a constituent a gas that substantially causes no impurity in the discharge gas; and a substep for re-  
25 evacuating the envelope.

Also, the present invention is a method of

producing a gas discharge panel that includes: an  
envelope forming step for forming an envelope by  
providing over a first plate a second plate so that the  
second plate faces a main surface of the first plate, on  
5 which partition walls for partitioning light emitting  
cells have been formed; a sealing step for sealing the  
envelope with a sealant along outer edges of the first  
and second plates; an exhaust step for exhausting gas  
from the envelope; and a filling step for filling the  
10 envelope with a discharge gas, wherein the exhaust step  
includes: a substep for evacuating the envelope; and a  
substep for exhausting gas from the envelope while a  
cleaning gas is circulated through the envelope, the  
cleaning gas including as a constituent a gas that  
15 substantially causes no impurity in the discharge gas.

Unlike the conventional method, gas is not only  
exhausted from the envelope as in the case of the  
conventional producing method. According to these  
producing methods, gas is exhausted from the envelope  
20 after the envelope is filled with the cleaning gas or  
while the cleaning gas is circulated through the  
envelope. As a result, the concentration of impurity gas  
in the envelope can be swiftly (in a short period of  
time) lowered compared with the conventional method. The  
25 higher definition the gas discharge panel, the more  
significant the effective. This is because it takes

longer to lower the impurity gas concentration as the definition is increased in general.

Note that when gas is exhaust from the envelope after the envelope is filled with the cleaning gas, it is more preferable to exhaust gas after a certain period of time has elapsed since the envelope is filled with the cleaning gas.

Here, the sealant can be disposed between the first and second plates, the entire envelope can be heated at a temperature that is no lower than one of a softening point and a melting point of the sealant while a pressure in the envelope can be set lower than a pressure outside of the envelope, and the envelope can be cooled at the sealing step. Note that lead alloy can be used as the sealant.

As a result, the envelope is sealed so that the entire top ends of the partition walls almost come in contact with the plate that faces the partition walls.

Here, a step for inserting a getter into a container that is linked to an internal space of the envelope can be included between the sealing step and the exhaust step.

As a result, the impurity gas can be removed from the envelope more swiftly.

Here, the entire envelope can be heated at a temperature that is no higher than one of a softening

point and a melting point of the sealant at the exhaust<sup>step</sup>. Note that when the getter is used as in the case described above, it is preferable that the activation temperature of the getter is within the range of the heating temperature.

As a result, the impurity can be removed from the envelope more swiftly.

Here, the entire envelope can be cooled to a temperature that is higher than room temperature and no higher than one of the softening point and the melting point of the sealant at the sealing step.

By doing so, a process in which the temperature is lowered to the room temperature once and then increased to the exhaust baking temperature is not included the processing. As a result, the processing can advance to the next step, the exhaust step earlier.

Here, the sealing step can include: a substep for disposing the sealant between the first and second plates, and heating the entire envelope to a temperature that is no lower than one of a softening point and a melting point of the sealant while a dry gas is circulated through the envelope; and a substep for heating the entire envelope at a temperature that is no lower than one of the softening point and the melting point of the sealant while a pressure in the envelope is set to be lower than a pressure outside of the envelope,

and cooling the envelope.

By doing so, the sealing step is performed while the envelope is filled with the dry gas. As a result, the heat deterioration of the phosphors can be prevented.

5 Here, the sealant can be disposed between the first and second plates, sealed edges of the first and second plates can be heated at a temperature that is no lower than one of a softening point and a melting point of the sealant while a pressure in the envelope is set  
10 lower than a pressure outside of the envelope, and the envelope can be cooled at the sealing step.

Here, it is most preferable to use the discharge gas as the cleaning gas.

This is because there is no possibility that the  
15 cleaning gas is an impurity gas for the discharge gas with which the envelope is filled at the filling step, which comes after the exhaust step.

Here, a noble gas can be used as the discharge gas.

20 Here, the noble gas can include at least one of helium, neon, argon, and xenon.

Here, the light emitting cells can be formed by positioning a first group of parallel electrodes on the first plate orthogonally to a second group of parallel  
25 electrodes on the second plate with a distance between the first and second electrode groups.

Although the present invention has been fully described by way of examples with reference to the accompanying drawings, it is to be noted that various changes and modifications will be apparent to those skilled in the art. Therefore, unless such changes and modifications depart from the scope of the present invention, they should be construed as being included therein.

#### 10 INDUSTRIAL USE POSSIBILITY

The method of producing gas discharge panel according to the present invention can be applied to manufacturing the PDP and the like that is used as the display such as the monitor of the TV set, the computer, and the like.



## CLAIMS

1 1. A method of producing a gas discharge panel,  
2 comprising:

3 an envelope forming step for forming an envelope  
4 by providing over a first plate a second plate so that  
5 the second plate faces a main surface of the first plate,  
6 on which partition walls for partitioning light emitting  
7 cells have been formed;

8 a sealing step for sealing the envelope with a  
9 sealant along outer edges of the first and second plates;

10 an exhaust step for exhausting gas from the  
11 envelope; and

12 a filling step for filling the envelope with a  
13 discharge gas, wherein

14 the exhaust step includes:

15 a substep for evacuating the envelope;

16 a substep for filling the envelope with a  
17 cleaning gas that includes as a constituent a gas that  
18 substantially causes no impurity in the discharge gas;  
19 and

20 a substep for re-evacuating the envelope.

1 2. A method of producing a gas discharge panel,  
2 comprising:

3 an envelope forming step for forming an envelope

4 by providing over a first plate a second plate so that  
5 the second plate faces a main surface of the first plate,  
6 on which partition walls for partitioning light emitting  
7 cells have been formed;

8 a sealing step for sealing the envelope with a  
9 sealant along outer edges of the first and second plates;

10 an exhaust step for exhausting gas from the  
11 envelope; and

12 a filling step for filling the envelope with a  
13 discharge gas, wherein

14 the exhaust step includes:

15 a substep for evacuating the envelope; and

16 a substep for exhausting gas from the envelope  
17 while a cleaning gas is circulated through the envelope,  
18 the cleaning gas including as a constituent a gas that  
19 substantially causes no impurity in the discharge gas.

1 3. The gas discharge panel producing method  
2 according to Claim 1, wherein the sealant is disposed  
3 between the first and second plates, the entire envelope  
4 is heated at a temperature that is no lower than one of a  
5 softening point and a melting point of the sealant while  
6 a pressure in the envelope is set lower than a pressure  
7 outside of the envelope, and the envelope is cooled at  
8 the sealing step.

4. The gas discharge panel producing method according to Claim 2, wherein the sealant is disposed between the first and second plates, the entire envelope is heated at a temperature that is no lower than one of a softening point and a melting point of the sealant while a pressure in the envelope is set lower than a pressure outside of the envelope, and the envelope is cooled at the sealing step.

5. The gas discharge panel producing method according to Claim 1, wherein a step for inserting a getter into a container that is linked to an internal space of the envelope is included between the sealing step and the exhaust step.

6. The gas discharge panel producing method according to Claim 2, wherein a step for inserting a getter into a container that is linked to an internal space of the envelope is included between the sealing step and the exhaust step.

7. The gas discharge panel producing method according to Claim 3, wherein a step for inserting a getter into a container that is linked to an internal space of the envelope is included between the sealing step and the exhaust step.

8. The gas discharge panel producing method according to Claim 4, wherein a step for inserting a getter into a container that is linked to an internal space of the envelope is included between the sealing step and the exhaust step.

9. The gas discharge panel producing method according to Claim 1, wherein the entire envelope is heated at a temperature that is no higher than one of a softening point and a melting point of the sealant at the exhaust step.

10. The gas discharge panel producing method according to Claim 2, wherein the entire envelope is heated at a temperature that is no higher than one of a softening point and a melting point of the sealant at the exhaust step.

11. The gas discharge panel producing method according to Claim 3, wherein the entire envelope is heated at a temperature that is no higher than one of the softening point and the melting point of the sealant at the exhaust step.

12. The gas discharge panel producing method

2 according to Claim 4, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 13. The gas discharge panel producing method  
2 according to Claim 5, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of a  
4 softening point and a melting point of the sealant at the  
5 exhaust step.

1 14. The gas discharge panel producing method  
2 according to Claim 6, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of a  
4 softening point and a melting point of the sealant at the  
5 exhaust step.

1 15. The gas discharge panel producing method  
2 according to Claim 7, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 16. The gas discharge panel producing method  
2 according to Claim 8, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the

4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 17. The gas discharge panel producing method  
2 according to Claim 3, wherein the entire envelope is  
3 cooled to a temperature that is higher than room  
4 temperature and no higher than one of the softening point  
5 and the melting point of the sealant at the sealing step.

1 18. The gas discharge panel producing method  
2 according to Claim 4, wherein the entire envelope is  
3 cooled to a temperature that is higher than room  
4 temperature and no higher than one of the softening point  
5 and the melting point of the sealant at the sealing step.

1 19. The gas discharge panel producing method  
2 according to Claim 11, wherein the entire envelope is  
3 cooled to a temperature that is higher than room  
4 temperature and no higher than one of the softening point  
5 and the melting point of the sealant at the sealing step.

1 20. The gas discharge panel producing method  
2 according to Claim 12, wherein the entire envelope is  
3 cooled to a temperature that is higher than room  
4 temperature and no higher than one of the softening point  
5 and the melting point of the sealant at the sealing step.

21. The gas discharge panel producing method according to Claim 1, wherein the sealing step includes:

a substep for disposing the sealant between the first and second plates, and heating the entire envelope to a temperature that is no lower than one of a softening point and a melting point of the sealant while a dry gas is circulated through the envelope; and

a substep for heating the entire envelope at a temperature that is no lower than one of the softening point and the melting point of the sealant while a pressure in the envelope is set to be lower than a pressure outside of the envelope, and cooling the envelope.

22. The gas discharge panel producing method according to Claim 2, wherein the sealing step includes:

a substep for disposing the sealant between the first and second plates, and heating the entire envelope to a temperature that is no lower than one of a softening point and a melting point of the sealant while a dry gas is circulated through the envelope; and

a substep for heating the entire envelope at a temperature that is no lower than one of the softening point and the melting point of the sealant while a pressure in the envelope is set to be lower than a

12 pressure outside of the envelope, and cooling the  
13 envelope.

1 23. The gas discharge panel producing method  
2 according to Claim 21, wherein a step for inserting a  
3 getter into a container that is linked to an internal  
4 space of the envelope is included between the sealing  
5 step and the exhaust step.

1 24. The gas discharge panel producing method  
2 according to Claim 22, wherein a step for inserting a  
3 getter into a container that is linked to an internal  
4 space of the envelope is included between the sealing  
5 step and the exhaust step.

1 25. The gas discharge panel producing method  
2 according to Claim 21, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 26. The gas discharge panel producing method  
2 according to Claim 22, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.



1 27. The gas discharge panel producing method  
2 according to Claim 23, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 28. The gas discharge panel producing method  
2 according to Claim 24, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 29. The gas discharge panel producing method  
2 according to Claim 21, wherein the entire envelope is  
3 cooled to a temperature that is higher than a room  
4 temperature and no higher than one of the softening point  
5 and the melting point of the sealant at the sealing step.

1 30. The gas discharge panel producing method  
2 according to Claim 22, wherein the entire envelope is  
3 cooled to a temperature that is higher than a room  
4 temperature and no higher than one of the softening point  
5 and the melting point of the sealant at the sealing step.

1 31. The gas discharge panel producing method

2 according to Claim 25, wherein the entire envelope is  
3 cooled to a temperature that is higher than a room  
4 temperature and no higher than one of the softening point  
5 and the melting point of the sealant at the sealing step.

1 32. The gas discharge panel producing method  
2 according to Claim 26, wherein the entire envelope is  
3 cooled to a temperature that is higher than a room  
4 temperature and no higher than one of the softening point  
5 and the melting point of the sealant at the sealing step.

1 33. The gas discharge panel producing method  
2 according to Claim 1, wherein the sealant is disposed  
3 between the first and second plates, sealed edges of the  
4 first and second plates are heated at a temperature that  
5 is no lower than one of a softening point and a melting  
6 point of the sealant while a pressure in the envelope is  
7 set lower than a pressure outside of the envelope, and  
8 the envelope is cooled at the sealing step.

1 34. The gas discharge panel producing method  
2 according to Claim 2, wherein the sealant is disposed  
3 between the first and second plates, sealed edges of the  
4 first and second plates are heated at a temperature that  
5 is no lower than one of a softening point and a melting  
6 point of the sealant while a pressure in the envelope is

7 set lower than a pressure outside of the envelope, and  
8 the envelope is cooled at the sealing step.

1 35. The gas discharge panel producing method  
2 according to Claim 33, wherein a step for inserting a  
3 getter into a container that is linked to an internal  
4 space of the envelope is included between the sealing  
5 step and the exhaust step.

1 36. The gas discharge panel producing method  
2 according to Claim 34, wherein a step for inserting a  
3 getter into a container that is linked to an internal  
4 space of the envelope is included between the sealing  
5 step and the exhaust step.

1 37. The gas discharge panel producing method  
2 according to Claim 33, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 38. The gas discharge panel producing method  
2 according to Claim 34, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 39. The gas discharge panel producing method  
2 according to Claim 35, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 40. The gas discharge panel producing method  
2 according to Claim 36, wherein the entire envelope is  
3 heated at a temperature that is no higher than one of the  
4 softening point and the melting point of the sealant at  
5 the exhaust step.

1 41. The gas discharge panel producing method  
2 according to one of Claims 1 to 40, wherein the cleaning  
3 gas is the discharge gas.

1 42. The gas discharge panel producing method  
2 according to Claim 41, wherein the discharge gas is a  
3 noble gas.

1 43. The gas discharge panel producing method  
2 according to Claim 42, wherein the noble gas includes at  
3 least one of helium, neon, argon, and xenon.

1 44. The gas discharge panel producing method

2 according to one of Claims 1 to 40, wherein the light  
3 emitting cells are formed by positioning a first group of  
4 parallel electrodes on the first plate orthogonally to a  
5 second group of parallel electrodes on the second plate  
6 with a distance between the first and second electrode  
7 groups.

1 45. The gas discharge panel producing method  
2 according to Claim 41, wherein the light emitting cells  
3 are formed by positioning a first group of parallel  
4 electrodes on the first plate orthogonally to a second  
5 group of parallel electrodes on the second plate with a  
6 distance between the first and second electrode groups.

1 46. The gas discharge panel producing method  
2 according to Claim 42, wherein the light emitting cells  
3 are formed by intersecting a first group of electrodes  
4 that have been disposed on the first plate in parallel  
5 and a second group of electrodes that have been disposed  
6 on the second plate in parallel with a distance between  
7 the first and second groups.

1 47. The gas discharge panel producing method  
2 according to Claim 43, wherein the light emitting cells  
3 are formed by intersecting a first group of electrodes  
4 that have been disposed on the first plate in parallel

5 and a second group of electrodes that have been disposed  
6 on the second plate in parallel with a distance between  
7 the first and second groups.

# ABSTRACT

A method of producing a gas discharge panel capable of an efficient exhausting in the exhaust process. In a vacuum pumping process, with an open/close valve (53f) opened to a suitable degree while heating (baking) a heating furnace (51) to a temperature (exhaust baking temperature) lower than the softening temperature of a sealant layer, a turbo-molecular pump (53b) and a rotary pump (53c) are actuated to evacuate an envelope (40) until a vacuum is created, whereupon a discharge gas is introduced from a gas introducing system (52) into the envelope (40) until a predetermined pressure (for example, 0.05MPa) is produced therein. Thereafter, the discharge gas introduction from the gas introducing system (52) is stopped, and the discharge gas in the envelope is sucked out through a suction exhaust system (53), thereby re-establishing a vacuum state in the envelope (40).

09/744227




FIG. 1

09/744227



FIG.2





FIG.3



09/744227




FIG. 4

09/744227

FIG. 5




FIG.6




FIG. 7





FIG.8



Docket No.

# Declaration and Power of Attorney For Patent Application

## English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD OF PRODUCING GAS DISCHARGE PANEL

the specification of which

(check one)

☐ is attached hereto.

☒ was filed on May 17, 2000 as United States Application No. or PCT International Application Number PCT/JP00/03154 and was amended on \_\_\_\_\_

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

<u>11-139719</u>	<u>Japan</u>	<u>20/May/1999</u>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	
<u>11-147937</u>	<u>Japan</u>	<u>27/May/1999</u>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	
_____	_____	_____	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	



I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

\_\_\_\_\_  
(Application Serial No.)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Application Serial No.)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Application Serial No.)

\_\_\_\_\_  
(Filing Date)

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112, I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

\_\_\_\_\_  
(Application Serial No.)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Status)  
(patented, pending, abandoned)

\_\_\_\_\_  
(Application Serial No.)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Status)  
(patented, pending, abandoned)

\_\_\_\_\_  
(Application Serial No.)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Status)  
(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. *(list name and registration number)*

Joseph W. Price, Reg. No. 25,124

Doyle B. Johnson, Reg. No. 39,240

Albin H. Gess, Reg. No. 25,726

Michael J. Moffatt, Reg. No. 39,304

Franklin D. Ubell, Reg. No. 27,009

Bradley D. Blanche, Reg. No. 38,387

Send Correspondence to: Joseph W. Price  
PRICE, GESS & UBELL  
2100 S.E. Main St., Ste. 250  
Irvine, CA 92614

Direct Telephone Calls to: *(name and telephone number)*  
Joseph W. Price, 949/261-8433

Full name of sole or first inventor		<u>Hidetaka HIGASHINO</u>
Sole or first inventor's signature		<u>Hidetaka Higashino</u> Date <u>January 15, 2001</u>
Residence		<u>31-9, Hikaridai 7-chome, Seikacho, Souraku-gun, Kyoto 619-0237 Japan</u> JPX
Citizenship		<u>Japan</u>
Post Office Address		<u>same as residence</u>

Full name of second inventor, if any		<u>Nobuaki NAGAO</u>
Second inventor's signature		<u>Nobuaki Nagao</u> Date <u>January 15, 2001</u>
Residence		<u>3-205, Myoukenzaka 3-chome, Katano-shi, Osaka 576-0021 Japan</u> JPX
Citizenship		<u>Japan</u>
Post Office Address		<u>same as residence</u>



CATEGORY:

**CLEARED**

---

ADDRESS  
CONTACT IF FOUND:

---




FIG.1

09/74227




FIG.4